

Batteriekabel MATRIX

Ringösendurchmesser **M8/M8**

| Kabelquerschnitt | 35 mm ² | | | | 50 mm ² | | | | 70 mm ² | | | | | | | | | | | | | | | |
|------------------|--------------------|----------|----------|----------|--------------------|----------|----------|----------|--------------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| | 300 A | | | | 450 A | | | | 600 A | | | | | | | | | | | | | | | |
| | 700 A | | | | 1000 A | | | | 1500 A | | | | | | | | | | | | | | | |
| Kabellängen | 15 cm | 30 cm | 60 cm | 130 cm | 15 cm | 30 cm | 60 cm | 130 cm | 15 cm | 30 cm | 60 cm | 130 cm | | | | | | | | | | | | |
| Kabelfarbe | Red | Black | Black | Black | Red | Black | Black | Black | Red | Black | Black | Black | | | | | | | | | | | | |
| Artikelnummer | 400-1220 | 400-1221 | 400-1222 | 400-1223 | 400-1224 | 400-1225 | 400-1226 | 400-1227 | 400-1228 | 400-1229 | 400-1230 | 400-1231 | 400-1232 | 400-1233 | 400-1234 | 400-1235 | 400-1236 | 400-1237 | 400-1238 | 400-1239 | 400-1240 | 400-1241 | 400-1242 | 400-1243 |

Ringösendurchmesser **M8/M10**

| Kabelquerschnitt | 35 mm ² | | | | 50 mm ² | | | | 70 mm ² | | | | | | | | | | | | | | | |
|------------------|--------------------|----------|----------|----------|--------------------|----------|----------|----------|--------------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| | 300 A | | | | 450 A | | | | 600 A | | | | | | | | | | | | | | | |
| | 700 A | | | | 1000 A | | | | 1500 A | | | | | | | | | | | | | | | |
| Kabellängen | 15 cm | 30 cm | 60 cm | 130 cm | 15 cm | 30 cm | 60 cm | 130 cm | 15 cm | 30 cm | 60 cm | 130 cm | | | | | | | | | | | | |
| Kabelfarbe | Red | Black | Black | Black | Red | Black | Black | Black | Red | Black | Black | Black | | | | | | | | | | | | |
| Artikelnummer | 400-1244 | 400-1245 | 400-1246 | 400-1247 | 400-1248 | 400-1249 | 400-1250 | 400-1251 | 400-1252 | 400-1253 | 400-1254 | 400-1255 | 400-1256 | 400-1257 | 400-1258 | 400-1259 | 400-1260 | 400-1261 | 400-1262 | 400-1263 | 400-1264 | 400-1265 | 400-1266 | 400-1267 |

Material Kabelmantel **PVC**

Temperaturbereich
 Min. **-35 °C** Max. **105 °C**

Zulässige Spannung
12 V | 24 V | 36 V | 48 V

Litzendurchmesser
~0,12 mm²

UV
 Beständig

Material Ringöse **CuNi**

