

# Batteriekabel MATRIX

Ringösendurchmesser **M8/M8**

Kabelquerschnitt	35 mm <sup>2</sup>				50 mm <sup>2</sup>				70 mm <sup>2</sup>															
	300 A				450 A				600 A															
	700 A				1000 A				1500 A															
Kabellängen	15 cm	30 cm	60 cm	130 cm	15 cm	30 cm	60 cm	130 cm	15 cm	30 cm	60 cm	130 cm												
Kabelfarbe	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red												
Artikelnummer	400-1220	400-1221	400-1222	400-1223	400-1224	400-1225	400-1226	400-1227	400-1228	400-1229	400-1230	400-1231	400-1232	400-1233	400-1234	400-1235	400-1236	400-1237	400-1238	400-1239	400-1240	400-1241	400-1242	400-1243

Ringösendurchmesser **M8/M10**

Kabelquerschnitt	35 mm <sup>2</sup>				50 mm <sup>2</sup>				70 mm <sup>2</sup>															
	300 A				450 A				600 A															
	700 A				1000 A				1500 A															
Kabellängen	15 cm	30 cm	60 cm	130 cm	15 cm	30 cm	60 cm	130 cm	15 cm	30 cm	60 cm	130 cm												
Kabelfarbe	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red												
Artikelnummer	400-1244	400-1245	400-1246	400-1247	400-1248	400-1249	400-1250	400-1251	400-1252	400-1253	400-1254	400-1255	400-1256	400-1257	400-1258	400-1259	400-1260	400-1261	400-1262	400-1263	400-1264	400-1265	400-1266	400-1267

Material Kabelmantel **PVC**

Temperaturbereich  
 Min. **-35 C°** Max. **105 C°**

Zulässige Spannung  
**12 V | 24 V | 36 V | 48 V**

Litzendurchmesser  
**~0,12 mm<sup>2</sup>**

**UV**  
 Beständig

Material Ringöse **CuNi**

